

CENTRA AND CENTRA-XL POWER SUPPLIES

Centra 15v DC

<p>Wall Adapter / Indoor Use</p> <p>TLD-24WSI 24 Watt Power Supply</p>  <p>Length: 3" Width: 2.125" Depth: 1.25" Wire Length: 72" 2 year limited warranty</p>	<p>Indoor / Damp IP64</p> <p>Can accommodate 120V AC to 277V AC</p> <p>TLD-30WSO 30 Watt Power Supply Hardwire Length: 7.0" Width: 2.3" Depth: 1.1"</p> <p>TLD-60WSO 60 Watt Power Supply Hardwire Length: 8.0" Width: 2.4" Depth: 1.4" 2 year limited warranty</p> <p>TLD-75WSO 75 Watt Power Supply Hardwire Length: 8.5" Width: 2.7" Depth: 1.7"</p>
<p>Wall Plug / Indoor Use</p> <p>TLD-60W-PLG2 60 Watt Power Supply</p>  <p>Length: 5.0" Width: 2.0" Depth: 1.25" Wall Plug: 6' Low Voltage Wire: 38" 2 year limited warranty</p> <p>TLD-90W-PLG 90 Watt Power Supply</p>  <p>Length: 5.0" Width: 2.0" Depth: 1.25" Wall Plug: 6' Low Voltage Wire: 38"</p>	<p>Outdoor / Waterproof IP67</p> <p>TLD-120WSO-PLG-15 120 Watt Power Supply</p>  <p>Length: 17.0" - Width: 2.75" - Depth: 1.5" Power cord is 6' long Plug into existing GFI duplex outlet 2 year limited warranty</p> <p>TLD-120WSO-JNC-15 120 Watt Power Supply Hardwire</p>  <p>Length: 14.5" - Width: 2.75" - Depth: 1.5" Includes onboard junction boxes for hardwire 2 year limited warranty</p>

CentraXL 24v DC


<p>TLD 24WSI-24 24 Watt Power Supply Wall adaptor Length: 3" Width: 2.125" Depth: 1.25" Wire Length: 72"</p>	<p>Wall Plug Wall Plug: 6' Low Voltage Wire: 38"</p>	<p>TLD-40W-PLG-24 40 Watt Power Supply</p> <p>TLD-60W-PLG-24 60 Watt Power Supply</p> <p>TLD-90W-PLG-24 90 Watt Power Supply</p>	<p>L W H (inches)</p> <p>5 x 2 x 1.25</p> <p>5 x 2 x 1.25</p> <p>7 x 2.3 x 1.25</p> <p>TLD-30WSO-24 30 Watt Power Supply</p> <p>TLD-90WSO-24 90 Watt Power Supply</p> <p>IP64 Rating</p> <p>Length: 15" - Width: 2.75" - Depth: 1.5" Includes onboard junction boxes for hardwire 2 year limited warranty</p>
---	---	---	---

Outdoor Use / Waterproof IP67

<p>TLD-60WSO-24-WP 60 Watt Power Supply</p> <p>TLD-120WSO-24 120 Watt Power Supply</p> <p>TLD-150WSO-24 150 Watt Power Supply</p> <p>TLD-240WSO-24 240 Watt Power Supply</p>	<p>Hard Wire</p> <p>L W H (inches)</p> <p>6.75 x 2.5 x 1.5</p> <p>8.5 x 2.75 x 1.5</p> <p>9 x 2.75 x 1.5</p> <p>9 x 2.75 x 1.5</p>	<p>TLD-240WSO-PLG-24 240 Watt Power Supply</p> <p>Length: 18.0" - Width: 2.75" - Depth: 1.5" Power cord is 6' long Plug into existing GFI duplex outlet 2 year limited warranty</p>	<p>TLD-240WSO-JNC-24 240 Watt Power Supply</p> <p>Hardwire</p> <p>Length: 15" - Width: 2.75" - Depth: 1.5" Includes onboard junction boxes for hardwire 2 year limited warranty</p>
2 year limited warranty			

Acceptable Voltage Drop and Wire Gauge

Tables Based on Single Power Supply



Denotes Design Light Level (13.5 to 15.0 VDC)
 Denotes 50% to 80% Light Level (12.0 to 13.4 VDC)
 Denotes Less Than 50% Light Level (Under 12.0 VDC)